enmach

SPECIFICATION

DPRV80S-MK DIESEL TANK

- Slimline Tank
- Roto Moulded Diesel Grade Yellow Polyethylene
- 3/4" Brass Outlets & 3/8" Plastic Thread breather
- 1 1/2" Inlet
- Mount Kit Included
- Approximate Usable Storage-80 Litres
- Size: L x 1080mm, W x 835mm, H x 115mm
- Filling & Fitting Instructions:

Drill and bolt mounting angles supplied to tray or chassis at the right width and fix tank to angles using bolts supplied. Fix support bracket to the underside of tank using centre bolts on the mounting angles.

This tank is not to be pressure filled from a hose that is connected from mains pressure to the tank that has a larger flow rate than the breather. Doing so will cause the tank to inflate and split and will void warranty.

We recommend to use plastic/nylon fittings in this tank not brass.

The stated litre capacity is by cubic measurements and is a guide only. Usable litre capacity is determined by the way the tank is mounted.

TANK MUST BE FLUSHED BEFORE INITIAL USE





Call us today on Freecall enmach 1800 502 267 17 CHARLIE TRIGGS CRESCENT **BUNDABERG QLD 4670** FAX: 07 4153 0900 EMAIL: sales@enmach.com.au

www.enmach.com.au